

The pdfcrypt package

Heiko Oberdiek*

2016/05/16 v1.1

Abstract

This package supports the setting of pdf encryption options for V $\text{T}_{\text{E}}\text{X}$ and some older versions of pdf $\text{T}_{\text{E}}\text{X}$.

Contents

1	Documentation	2
1.1	Alternatives	2
1.2	Usage	2
1.2.1	Special characters	3
1.2.2	<code>\nopdfcrypt</code>	3
1.2.3	Configuration file	3
1.2.4	Support for plain $\text{T}_{\text{E}}\text{X}$	3
1.3	Hints for pdf $\text{T}_{\text{E}}\text{X}$	3
2	Implementation	4
2.1	Help macros for plain $\text{T}_{\text{E}}\text{X}$	4
2.2	Package Identification and checks	5
2.3	Driver detection	6
2.4	Load package <code>keyval</code>	6
2.5	Define options	7
2.6	support of configuration file	12
2.7	Package options	12
3	Installation	12
3.1	Download	12
3.2	Bundle installation	13
3.3	Package installation	13
3.4	Refresh file name databases	13
3.5	Some details for the interested	13
4	History	14
	[2001/04/02 v0.1]	14
	[2001/07/19 v0.2]	14
	[2001/07/19 v0.3]	14
	[2001/07/19 v0.4]	14
	[2001/08/05 v0.5]	14
	[2001/08/09 v0.6]	14
	[2001/10/28 v0.7]	14
	[2006/02/20 v0.8]	15

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

[2007/04/11 v0.9]	15
[2007/04/26 v1.0]	15
[2016/05/16 v1.1]	15
5 Index	15

1 Documentation

This package allows the setting of pdf encryption options for

- V_TE_X, since version 7.35, <http://www.micropress-inc.com/>.
- pdf_TE_X, patched by Ricardo Sanchez Carmenes¹.
Some supported versions are:

pdf_TE_X-1.00a,
pdf_TE_X-0.14h-pdfcrypt-20010310,
pdfcrypt-20010331

Note: Since pdf_TE_X-1.10a (2003-01-16) encryption support was dropped! Thus the package is now obsolete for recent pdf_TE_X versions.

1.1 Alternatives

There are free alternatives, programs that can be used for postprocessing the pdf file:

- pdftk
<http://www.accesspdf.com/pdftk/>
- Multivalent
<http://multivalent.sourceforge.net/>
- PDFBox
<http://www.pdfbox.org/>
- PDFTrans
<http://maddingue.free.fr/software/pdftrans.html>
- ...

1.2 Usage

The options can be set as package options or with the command `\pdfcryptsetup`:

```
owner=<owner password>
user=<user password>
print, copy, edit, annotate=true, false
all, none
debug
```

The encryption is set at `\begin{document}` by default, but this can be forced for an earlier time using the option `set`. Example:

```
\usepackage[owner=Donald,user=Knuth,print=false]{pdfcrypt}
...
\begin{document}
```

¹Ricardo Sanchez Carmenes's email address: carmenes@bioquimica.uniovi.es

or

```
\usepackage{pdfcrypt}
\pdfcryptsetup{owner=Donald,user=Knut}
\pdfcryptsetup{print=false,set}
...
\begin{document}
```

1.2.1 Special characters

The characters ‘{’, ‘}’, and ‘\’ have to be escaped with ‘\’. Then the string should not be specified as package option but with the macro `\pdfcryptsetup`, eg:

```
\pdfcryptsetup{user={\{\Hello\}},print=false}
```

The password here is “`{\Hello}`”. Active characters can be used and are not expanded. Macros except for `\{`, `\}`, and `\\` should not be used and are not expanded.

1.2.2 `\nopdfcrypt`

Often the whole process of pdf generation includes several $\text{T}_{\text{E}}\text{X}$ compilations and perhaps other postprocessing steps. Therefore a feature would be useful to disable the encryption stuff in order to speed up the first compilations. Therefore package `pdfcrypt` will look for the macro `\nopdfcrypt`. If it has the meaning of the letter ‘Y’, the package will be disabled. Example:

```
pdflatex '\let\nopdfcrypt=Y\input myfile'
thumbpdf myfile
pdfelatex myfile
```

1.2.3 Configuration file

If the file `pdfcrypt.cfg` exists it is loaded and can be used for common settings.

1.2.4 Support for plain $\text{T}_{\text{E}}\text{X}$

The package can also be used with plain $\text{T}_{\text{E}}\text{X}$. It defines the missing $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ macros and loads package `keyval`. The configuration file is not supported and automatically loaded.

1.3 Hints for pdf $\text{T}_{\text{E}}\text{X}$

This section is out of date, because the encryption support was removed from pdf $\text{T}_{\text{E}}\text{X}$. Therefore this hints are of historical interest only.

* There are packages such as `thumbpdf` that ship out some stuff (`\immediate\pdfobj{...}`). In these cases `\pdfcrypt` will be ignored without warning or error message. Therefore the package `pdfcrypt` should be loaded before and option "set" should be used in order to force the call of `\pdfcrypt`, for example:

```
\usepackage{pdfcrypt}
\pdfcryptsetup{..., set}
...
\usepackage{thumbpdf}
```

```

* Compiling pdfTeX (eg. version 1.00a-pretest-20010804):
pdfTeX versions are available at
  ftp://ftp.cstug.cz/pub/tex/local/cstug/thanh/pdftex/snapshots/
Unpack the latest .tgz file:
  > tar xzf pdftex-20010804.tgz
Enable encryption support:
  src> cd src/texk/web2c/pdftexdir
  src/texk/web2c/pdftexdir> ln -fs pdfcrypt-full.c pdfcrypt.c
Compile:
  src/texk/web2c/pdftexdir> cd ../../..
  src> ./configure
  src> cd texk/web2c
  src/texk/web2c> make pdftexbin
At last install the binary and pool files.

```

2 Implementation

```
1 (*package)
```

2.1 Help macros for plain T_EX

```

2 \expandafter\edef\csname pc@endinput\endcsname{%
3   \catcode'\noexpand\@=\the\catcode'\@relax
4   \noexpand\endinput
5 }
6 \catcode'\@=11 %
7
8 \expandafter\ifx\csname @firstoftwo\endcsname\relax
9   \long\def\@firstoftwo#1#2{#1}%
10 \fi
11
12 \expandafter\ifx\csname @secondoftwo\endcsname\relax
13   \long\def\@secondoftwo#1#2{#2}%
14 \fi
15
16 \expandafter\ifx\csname @ifundefined\endcsname\relax
17   \def\@ifundefined#1{%
18     \expandafter\ifx\csname #1\endcsname\relax
19       \expandafter\@firstoftwo
20     \else
21       \expandafter\@secondoftwo
22     \fi
23   }%
24 \fi
25
26 \@ifundefined{@ifnextchar}{%
27   \long\def\@ifnextchar#1#2#3{%
28     \let\reserved@d=#1%
29     \def\reserved@a{#2}%
30     \def\reserved@b{#3}%
31     \futurelet\@let@token\@ifnch
32   }%
33   \def\@ifnch{%
34     \ifx\@let@token\@sptoken
35       \let\reserved@c\@xifnch
36     \else
37       \ifx\@let@token\reserved@d
38         \let\reserved@c\reserved@a

```

```

39     \else
40         \let\reserved@c\reserved@b
41     \fi
42 \fi
43 \reserved@c
44 }%
45 \begingroup
46 \def\:\{\global\let\@sptoken= }%
47 \: %
48 \def\:\{\@xifnch}%
49 \expandafter\gdef\:\ {\futurelet\@let@token\@ifnch}%
50 \endgroup
51 }{}
52
53 \@ifundefined{ProvidesPackage}{%
54 \def\ProvidesPackage#1{%
55 \ifnextchar[{\pc@ProvidesPackage{#1}}%
56 \{\pc@ProvidesPackage{#1}[]}%
57 }%
58 \def\pc@ProvidesPackage#1[#2]{%
59 \immediate\write-1{Package: #1 #2}%
60 }%
61 }{}
62
63 \begingroup\expandafter\expandafter\expandafter\endgroup
64 \expandafter\ifx\csname RequirePackage\endcsname\relax
65 \input infwarerr.sty\relax
66 \else
67 \RequirePackage{infwarerr}%
68 \fi
69
70 \@ifundefined{@gobble}{%
71 \long\def@gobble#1{}%
72 }{}
73
74 \@ifundefined{@empty}{%
75 \def@empty{}%
76 }{}

```

2.2 Package Identification and checks

```

77 \ProvidesPackage{pdfcrypt}%
78 [2016/05/16 v1.1 Allows the setting of PDF encryption (HO)]%
79 \@ifundefined{pdfcryptsetup}{%
80 \let\pdfcryptsetup@gobble
81 }{}%
82 \@PackageWarningNoLine{pdfcrypt}{Package pdfcrypt is already loaded}%
83 \pc@endinput
84 }

```

Support for \nopdfcrypt.

```

85 \newif\ifpc@nopdfcrypt
86 \ifx Y\nopdfcrypt
87 \@PackageWarningNoLine{pdfcrypt}{%
88 Encryption disabled by \string \nopdfcrypt\space request%
89 }%
90 \global\pc@nopdfcrypttrue
91 \fi

```

2.3 Driver detection

```
92 \let\pc@driver\@empty
93 \begingroup
94 % pdfTeX detection
95 \@ifundefined{pdfoutput}{%
96 }{%
97   \ifcase\pdfoutput
98   \else
99     \@ifundefined{pdfcrypt}{%
100       \PackageError{pdfcrypt}{%
101         PDF encryption is not supported with this pdfTeX%
102       }{%
103         Encryption support was added in 0.14h (2001/03/10)\MessageBreak
104         and removed in 1.10a (2003/01/16).%
105       }%
106     \endgroup
107     \pc@endinput
108   }{%
109     \gdef\pc@driver{pdftex}%
110   }%
111   \fi
112 }%
113 % VTeX detection
114 \@ifundefined{OpMode}{%
115 }{%
116   \ifnum\OpMode=1 %
117     \ifnum\@ifundefined{VTeXversion}0\VTeXversion<735 %
118       \PackageError{pdfcrypt}{%
119         PDF encryption is not supported with this VTeX%
120       }{%
121         You need VTeX 7.35 or higher.%
122       }%
123     \endgroup
124     \pc@endinput
125   \else
126     \gdef\pc@driver{vtex}%
127   \fi
128   \fi
129 }%
130 \endgroup
```

2.4 Load package keyval

```
131 \@ifundefined{@makeother}{%
132   \def\@makeother#1{\catcode'#1=12\relax}%
133 }{}
134
135 \@ifundefined{g@addto@macro}{%
136   \long\def#g@addto@macro#1#2{%
137     \begingroup
138     \toks@\expandafter{#1#2}%
139     \xdef#1{\the\toks@}%
140     \endgroup
141   }%
142 }{}
143
144 \@ifundefined{@namedef}{%
145   \def\@namedef#1{\expandafter\def\csname#1\endcsname}%
146 }
```

```

146 }{}
147
148 \@ifundefined{@nameuse}{%
149   \def\@nameuse#1{\csname #1\endcsname}%
150 }{}
151
152 \def\pc@KeyvalRestore{%
153   \let\pc@KeyvalRestore\@undefined
154 }
155
156 \let\pcOrg@NeedsTeXFormat\NeedsTeXFormat
157 \@ifundefined{NeedsTeXFormat}{%
158   \def\NeedsTeXFormat#1{%
159     \g@addto@macro\pc@KeyvalRestore{%
160       \let\NeedsTeXFormat\pcOrg@NeedsTeXFormat
161     }%
162 }{}
163
164 \let\pcOrg@DeclareOption\DeclareOption
165 \@ifundefined{DeclareOption}{%
166   \def\DeclareOption#1#2{#2}%
167   \g@addto@macro\pc@KeyvalRestore{%
168     \let\DeclareOption\pcOrg@DeclareOption
169   }%
170 }{}
171
172 \let\pcOrg@ExecuteOptions\ExecuteOptions
173 \@ifundefined{ExecuteOptions}{%
174   \def\ExecuteOptions#1{%
175     \g@addto@macro\pc@KeyvalRestore{%
176       \let\ExecuteOptions\pcOrg@ExecuteOptions
177     }%
178 }{}
179
180 \let\pcOrg@ProcessOptions\ProcessOptions
181 \@ifundefined{ProcessOptions}{%
182   \def\ProcessOptions{%
183     \g@addto@macro\pc@KeyvalRestore{%
184       \let\ProcessOptions\pcOrg@ProcessOptions
185     }%
186 }{}%
187
188 \begingroup\expandafter\expandafter\expandafter\endgroup
189 \expandafter\ifx\csname RequirePackage\endcsname\relax
190   \input keyval.sty\relax
191 \else
192   \RequirePackage{keyval}%
193 \fi
194 \pc@KeyvalRestore

```

2.5 Define options

```

195 \@ifundefined{@dblarg}{%
196   \long\def\@dblarg#1{\@ifnextchar[{\#1}{\@xdblarg{\#1}}}%
197   \long\def\@xdblarg#1#2{#1[{\#2}]{\#2}}%
198 }{}
199
200 \newif\ifpc@set
201 \newif\ifpc@print

```

```

202 \newif\ifpc@copy
203 \newif\ifpc@edit
204 \newif\ifpc@annotate
205 \newif\ifpc@debug
206 \let\pc@owner\@empty
207 \let\pc@user\@empty
208
209 % default: allow all
210 \pc@printtrue
211 \pc@copytrue
212 \pc@edittrue
213 \pc@annotatetrue
214
215 \edef\pc@temp{\catcode'\noexpand\="=\the\catcode'\relax}
216 \@makeother\"
217 \def\pc@set{%
218   \@PackageInfo{pdfcrypt}{%
219     \ifpc@debug
220       \ifx\pc@owner\@empty
221         No owner password%
222       \else
223         Owner password: '\pc@owner'%
224       \fi
225     \MessageBreak
226     \ifx\pc@user\@empty
227       No user password%
228     \else
229       User password: '\pc@user'%
230     \fi
231     \MessageBreak
232     Flags: %
233     \ifpc@print   \else no\fi print, %
234     \ifpc@copy    \else no\fi copy, %
235     \ifpc@edit    \else no\fi edit, %
236     \ifpc@annotate\else no\fi annotate%
237     \MessageBreak
238     \fi
239     \ifpc@nopdfcrypt
240       Encryption is disabled by '\string\nopdfcrypt'%
241     \else
242       Encryption is set for '\pc@driver'%
243     \fi
244   }%
245   \ifpc@nopdfcrypt
246   \else
247     \@ifundefined{pc@set@\pc@driver}{%
248       \ifx\pc@driver\@empty
249         \@PackageError{pdfcrypt}{No driver for encryption %
250           support found}\@ehc
251       \else
252         \@PackageError{pdfcrypt}{Cannot set encryption for %
253           unknown driver '\pc@driver'}\@ehc
254       \fi
255     }{%
256       \@nameuse{pc@set@\pc@driver}%
257     }%
258   \fi
259 }

```



```

260 \def\pc@set@pdftex{%
261   \ifnum\pdftexversion<100 %
262     \pc@set@pdftexold
263   \else
264     \pc@set@pdftexnew
265   \fi
266 }
267 \def\pc@set@pdftexold{%
268   \pdfcrypt{%
269     owner "\pc@owner" %
270     user "\pc@user" %
271     \ifpc@print   \else no\fi print %
272     \ifpc@copy    \else no\fi copy %
273     \ifpc@edit    \else no\fi edit %
274     \ifpc@annotate\else no\fi annotate%
275   }%
276 }
277 \def\pc@set@pdftexnew{%
278   \pdfcrypt
279   owner{\pc@owner}%
280   user{\pc@user}%
281   \ifpc@print   \else no\fi print %
282   \ifpc@copy    \else no\fi copy %
283   \ifpc@edit    \else no\fi edit %
284   \ifpc@annotate\else no\fi annotate%
285   \relax
286 }
287 \def\pc@set@vtex{%
288   \immediate\special{!security %
289     O=\pc@MakeVTeXString\pc@owner,%
290     U=\pc@MakeVTeXString\pc@user,%
291     P\ifpc@print +\else -\fi,%
292     C\ifpc@copy +\else -\fi,%
293     M\ifpc@edit +\else -\fi,%
294     A\ifpc@annotate +\else -\fi
295   }%
296 }
297 \def\pc@MakeVTeXString#1{%
298   "\expandafter\pc@@MakeVTeXString#1"\@nil"
299 }
300 \def\pc@@MakeVTeXString#1"#2\@nil{%
301   #1%
302   \ifx\|#2\%
303     \else
304       "%
305       \@ReturnAfterFi{%
306         \pc@@MakeVTeXString#2\@nil
307       }%
308     \fi
309 }
310 \long\def\@ReturnAfterFi#1\fi{\fi#1}
311 \pc@temp
312
313 \begingroup
314   \catcode'\ =12 \gdef\pc@spaceother{ }\catcode'\ =10\relax
315   \catcode'\|=0 %
316   \catcode'\|=12 %
317   \gdef\pc@DefString#1#2{%

```

```

318 |def#1{#2}%
319 |edef#1{|expandafter|strip@prefix|meaning#1}%
320 |edef#1{|expandafter|pc@SpaceToOther#1 |@nil}%
321 |edef#1{|expandafter|pc@EscapeRemove#1|@empty\|@empty|@nil}%
322 }%
323 |gdef|pc@EscapeRemove#1\#2#3|@nil{%
324 #1#2%
325 |ifx|\#3|\%
326 |else
327 |@ReturnAfterFi{%
328 |pc@EscapeRemove#3|@nil
329 }%
330 |fi
331 }%
332 |endgroup
333 \def\pc@SpaceToOther#1 #2\@nil{%
334 #1%
335 \ifx\#2\%
336 \else
337 \pc@spaceother
338 \@ReturnAfterFi{%
339 \pc@SpaceToOther#2\@nil
340 }%
341 \fi
342 }
343
344 \def\pc@boolkey{\@dblarg\pc@@boolkey}
345 \def\pc@@boolkey[#1]#2#3{%
346 \lowercase{\def\pc@temp{#3}}%
347 \ifx\pc@temp\@empty
348 \let\pc@temp\pc@true
349 \fi
350 \ifx\pc@temp\pc@true
351 \else
352 \ifx\pc@temp\pc@false
353 \else
354 \let\pc@temp\relax
355 \fi
356 \fi
357 \ifx\pc@temp\relax
358 \@PackageWarning{pdfcrypt}{%
359 Unexpected value \string'#3\string' of %
360 option \string'#2\string'\MessageBreak
361 instead of %
362 \string'true\string' or \string'false\string'%
363 }%
364 \else
365 \csname pc@#2\pc@temp\endcsname
366 \fi
367 }
368 \def\pc@true{true}
369 \def\pc@false{false}
370
371 \define@key{pc}{set}[true]{%
372 \pc@boolkey{set}{#1}%
373 }
374 \define@key{pc}{pdftex}[]{%
375 \def\pc@driver{pdftex}%

```

```

376 }
377 \define@key{pc}{vtex}[]{}%
378 \def\pc@driver{vtex}%
379 }
380 \define@key{pc}{print}[true]{}%
381 \pc@boolkey{print}{#1}%
382 }
383 \define@key{pc}{copy}[true]{}%
384 \pc@boolkey{copy}{#1}%
385 }
386 \define@key{pc}{edit}[true]{}%
387 \pc@boolkey{edit}{#1}%
388 }
389 \define@key{pc}{annotate}[true]{}%
390 \pc@boolkey{annotate}{#1}%
391 }
392 \define@key{pc}{all}[]{}%
393 \pc@boolkey{print}{true}%
394 \pc@boolkey{copy}{true}%
395 \pc@boolkey{edit}{true}%
396 \pc@boolkey{annotate}{true}%
397 }
398 \define@key{pc}{none}[]{}%
399 \pc@boolkey{print}{false}%
400 \pc@boolkey{copy}{false}%
401 \pc@boolkey{edit}{false}%
402 \pc@boolkey{annotate}{false}%
403 }
404
405 \define@key{pc}{owner}{}%
406 \pc@DefString\pc@owner{#1}%
407 }
408 \define@key{pc}{user}{}%
409 \pc@DefString\pc@user{#1}%
410 }
411 \define@key{pc}{debug}[true]{}%
412 \pc@boolkey{debug}{#1}%
413 }
414
415 \def\pdfcryptsetup#1{}%
416 \setkeys{pc}{#1}%
417 \ifpc@set
418 \pc@set
419 \global\let\pc@set\relax
420 \gdef\pdfcryptsetup##1{}%
421 \@PackageWarning{pdfcrypt}{}%
422 Encryption options are already set\MessageBreak
423 new values are ignored%
424 }%
425 }%
426 \fi
427 }
428 \begingroup\expandafter\expandafter\expandafter\endgroup
429 \expandafter\ifx\cscname @onlypreamble\endcscname\relax
430 \else
431 \@onlypreamble\pdfcryptsetup
432 \fi

```

2.6 support of configuration file

```
433 \begingroup\expandafter\expandafter\expandafter\endgroup
434 \expandafter\ifx\csname InputIfFileExists\endcsname\relax
435   \@PackageInfo{pdfcrypt}{%
436     Configuration file pdfcrypt.cfg not supported.%
437   }%
438 \else
439   \let\pc@ExecuteOptions\ExecuteOptions
440   \InputIfFileExists{pdfcrypt.cfg}{-}{-}%
441   \let\ExecuteOptions\pc@ExecuteOptions
442 \fi
```

2.7 Package options

Plain format does not know package options.

```
443 \begingroup\expandafter\expandafter\expandafter\endgroup
444 \expandafter\ifx\csname @classoptionslist\endcsname\relax
445   \expandafter\pc@endinput
446 \fi
```

Process global and local options.

```
447 \def\pc@ProcessOptionsWithKV{%
448   \let\pc@temp\@empty
449   \@for\CurrentOption:=\@classoptionslist\do{%
450     \ifundefined{KV@pc@\CurrentOption}{-}{%
451       \edef\pc@temp{\pc@temp,\CurrentOption,}%
452       \@expandtwoargs\removeelement\CurrentOption
453       \@unusedoptionlist\@unusedoptionlist
454     }%
455   }%
456   \edef\pc@temp{%
457     \noexpand\pdfcryptsetup{%
458       \pc@temp\@optionlist{\@currname.\@current}%
459     }%
460   }%
461   \pc@temp
462 }
463 \pc@ProcessOptionsWithKV
464 \AtEndOfPackage{\let\@unprocessedoptions\relax}
465 \AtBeginDocument{\pc@set}
466
467 \pc@endinput
468 \</package>
```

3 Installation

3.1 Download

Package. This package is available on CTAN²:

CTAN:macros/latex/contrib/oberdiek/pdfcrypt.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/pdfcrypt.pdf Documentation.

²CTAN:pkg/pdfcrypt

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex pdfcrypt.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcrypt.sty → tex/generic/oberdiek/pdfcrypt.sty
pdfcrypt.pdf → doc/latex/oberdiek/pdfcrypt.pdf
pdfcrypt.dtx → source/latex/oberdiek/pdfcrypt.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (T_EX Live, MiK_TE_X, ...) relies on file name databases, you must refresh these. For example, T_EX Live users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{pdfcrypt.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
```

4 History

[2001/04/02 v0.1]

- First public version, published in the pdftex mailing list for testing with pdfcrypt-20010331

[2001/07/19 v0.2]

- Default: all allowed.
- Support for V_TE_X added.

[2001/07/19 v0.3]

- Bug fix: V_TE_X letter for edit is M (modify).

[2001/07/19 v0.4]

- Bug fix: `\TeXversion` is correct after regenerating the format file.

[2001/08/05 v0.5]

- Syntax change in pdfT_EX 1.00a.

[2001/08/09 v0.6]

- Support of special characters:
input: `\{, \}, \` for `{, }, \`
output: " in V_TE_X
- Option `debug` added.

[2001/10/28 v0.7]

- Plain compatibility.
- `\nopdfcrypt` added.
- Typos corrected.

[2006/02/20 v0.8]

- Obsolete remarks for pdfT_EX.
- DTX framework.
- LPPL 1.3

[2007/04/11 v0.9]

- Line ends sanitized.

[2007/04/26 v1.0]

- Use of package infwarerr.

[2016/05/16 v1.1]

- Documentation updates.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\"</code>	215, 216
<code>\#</code>	323, 325
<code>\%</code>	325
<code>\:</code>	46, 47, 48, 49
<code>\@</code>	3, 6
<code>\@PackageError</code>	100, 118, 249, 252
<code>\@PackageInfo</code>	218, 435
<code>\@PackageWarning</code>	358, 421
<code>\@PackageWarningNoLine</code>	82, 87
<code>\@ReturnAfterFi</code>	305, 310, 338
<code>\@classoptionslist</code>	449
<code>\@currentx</code>	458
<code>\@currname</code>	458
<code>\@dblarg</code>	196, 344
<code>\@ehc</code>	250, 253
<code>\@empty</code>	75, 92, 206, 207, 220, 226, 248, 347, 448
<code>\@expandtwoargs</code>	452
<code>\@firstoftwo</code>	9, 19
<code>\@for</code>	449
<code>\@gobble</code>	71, 80
<code>\@ifnch</code>	31, 33, 49
<code>\@ifnextchar</code>	27, 55, 196
<code>\@ifundefined</code>	17, 26, 53, 70, 74, 79, 95, 99, 114, 117, 131, 135, 144, 148, 157, 165, 173, 181, 195, 247, 450
<code>\@let@token</code>	31, 34, 37, 49
<code>\@makeother</code>	132, 216
<code>\@namedef</code>	145
<code>\@nameuse</code>	149, 256
<code>\@nil</code>	298, 300, 306, 333, 339
<code>\@onlypreamble</code>	431
<code>\@optionlist</code>	458
<code>\@removeelement</code>	452
<code>\@secondoftwo</code>	13, 21
<code>\@sptoken</code>	34, 46
<code>\@undefined</code>	153
<code>\@unprocessedoptions</code>	464
<code>\@unusedoptionlist</code>	453
<code>\@xdblarg</code>	196, 197
<code>\@xifnch</code>	35, 48
<code>\@</code>	302, 316, 335
<code>\ </code>	315, 321
<code>_</code>	314
A	
<code>\AtBeginDocument</code>	465
<code>\AtEndOfPackage</code>	464
C	
<code>\catcode</code> ..	3, 6, 132, 215, 314, 315, 316
<code>\csname</code>	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444
<code>\CurrentOption</code>	449, 450, 451, 452
D	
<code>\DeclareOption</code>	164, 166, 168
<code>\define@key</code>	371, 374, 377, 380, 383, 386, 389, 392, 398, 405, 408, 411

<code>\do</code>	449	<code>\pc@edittrue</code>	212
E		<code>\pc@endinput</code> ...	83, 107, 124, 445, 467
<code>\endcsname</code>	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444	<code>\pc@ExecuteOptions</code>	439, 441
<code>\endinput</code>	4	<code>\pc@false</code>	352, 369
<code>\ExecuteOptions</code>	172, 174, 176, 439, 441	<code>\pc@KeyvalRestore</code>	
F		. 152, 153, 159, 167, 175, 183, 194	
<code>\futurelet</code>	31, 49	<code>\pc@MakeVTeXString</code>	289, 290, 297
G		<code>\pc@nopdfcrypttrue</code>	90
<code>\g@addto@macro</code>	136, 159, 167, 175, 183	<code>\pc@owner</code>	
<code>\gdef</code>	49, 109, 126, 314, 420	. 206, 220, 223, 269, 279, 289, 406	
I		<code>\pc@printtrue</code>	210
<code>\ifcase</code>	97	<code>\pc@ProcessOptionsWithKV</code> ...	447, 463
<code>\ifnum</code>	116, 117, 261	<code>\pc@ProvidesPackage</code>	55, 56, 58
<code>\ifpc@annotate</code>	204, 236, 274, 284, 294	<code>\pc@set</code>	217, 418, 419, 465
<code>\ifpc@copy</code> ...	202, 234, 272, 282, 292	<code>\pc@set@pdftex</code>	260
<code>\ifpc@debug</code>	205, 219	<code>\pc@set@pdftexnew</code>	264, 277
<code>\ifpc@edit</code> ...	203, 235, 273, 283, 293	<code>\pc@set@pdftexold</code>	262, 267
<code>\ifpc@nopdfcrypt</code>	85, 239, 245	<code>\pc@set@vtex</code>	287
<code>\ifpc@print</code> ...	201, 233, 271, 281, 291	<code>\pc@spaceother</code>	314, 337
<code>\ifpc@set</code>	200, 417	<code>\pc@SpaceToOther</code>	333, 339
<code>\ifx</code>	8, 12, 16, 18, 34, 37, 64, 86, 189, 220, 226, 248, 302, 335, 347, 350, 352, 357, 429, 434, 444	<code>\pc@temp</code>	215, 311, 346, 347, 348, 350, 352, 354, 357, 365, 448, 451, 456, 458, 461
<code>\immediate</code>	59, 288	<code>\pc@true</code>	348, 350, 368
<code>\input</code>	65, 190	<code>\pc@user</code>	207, 226, 229, 270, 280, 290, 409
<code>\InputIfFileExists</code>	440	<code>\pc@Org@DeclareOption</code>	164, 168
L		<code>\pc@Org@ExecuteOptions</code>	172, 176
<code>\lowercase</code>	346	<code>\pc@Org@NeedsTeXFormat</code>	156, 160
M		<code>\pc@Org@ProcessOptions</code>	180, 184
<code>\MessageBreak</code>		<code>\pdfcrypt</code>	268, 278
.....	103, 225, 231, 237, 360, 422	<code>\pdfcryptsetup</code> .	80, 415, 420, 431, 457
N		<code>\pdfoutput</code>	97
<code>\NeedsTeXFormat</code>	156, 158, 160	<code>\pdftexversion</code>	261
<code>\newif</code> .	85, 200, 201, 202, 203, 204, 205	<code>\ProcessOptions</code>	180, 182, 184
<code>\nopdfcrypt</code>	86, 88, 240	<code>\ProvidesPackage</code>	54, 77
O		R	
<code>\OpMode</code>	116	<code>\RequirePackage</code>	67, 192
P		<code>\reserved@a</code>	29, 38
<code>\pc@@boolkey</code>	344, 345	<code>\reserved@b</code>	30, 40
<code>\pc@@MakeVTeXString</code> ...	298, 300, 306	<code>\reserved@c</code>	35, 38, 40, 43
<code>\pc@annotatetrue</code>	213	<code>\reserved@d</code>	28, 37
<code>\pc@boolkey</code>	344, 372, 381, 384, 387, 390, 393, 394, 395, 396, 399, 400, 401, 402, 412	S	
<code>\pc@copytrue</code>	211	<code>\setkeys</code>	416
<code>\pc@DefString</code>	406, 409	<code>\space</code>	88
<code>\pc@driver</code>	92, 109, 126, 242, 247, 248, 253, 256, 375, 378	<code>\special</code>	288
Q		T	
R		<code>\the</code>	3, 139, 215
S		<code>\toks@</code>	138, 139
T		V	
V		<code>\VTeXversion</code>	117
W		W	
<code>\write</code>	59		